## Подзапросы

## Простой подзапрос

#### 1 запрос

select price from titles where title = "Чтиво"

#### 2 запрос

select title, price from titles where price = \$6

#### Объеденный запрос

select title, price
from titles
where price =
(select price
from titles
where title = "Чтиво")

### Несколько уровней вложенности

#### Уровневый запрос

```
select au Iname, au fname
       from authors
      where au id in
        (select au id
       from titleauthor
       where title id in
         (select title id
           from titles
where type = "popular child"))
```

#### соединение

```
select au_lname, au_fname
    from authors, titles, titleauthor
where authors.au id = titleauthor.au id
 and titles.title id = titleauthor.title id
      and type = "popular child"
```

## Подзапросы в операторах модификации удаления и вставки

update titles
set price = price \* 2
where pub\_id in
(select pub\_id
from publishers
where pub\_name = "ОдесаДрук")

#### Соединение

set price = price \* 2 from titles, publishers where titles.pub\_id = publishers.pub\_id and pub\_name = "ОдесаДрук"

delete salesdetail
where title\_id in
(select title\_id
from titles
where type = "business")

#### соединение

delete salesdetail
from salesdetail, titles
where salesdetail.title\_id = titles.title\_id
and type = "business"

### Подзапросы в условных операторах

```
if exists (select title_id
from titles
where type = "business")
begin
delete salesdetail
where title_id in
(select title_id
from titles
where type = "business")
end
```

## Подзапросы-выражения

# **Использование коррелированных** подзапросов

select au\_Iname, au\_fname
from authors
where 100 in
(select royaltyper
from titleauthor
where au\_id = authors.au\_id)

select royaltyper from titleauthor where au\_id = "345"

from authors
where 100 in (100)