


The procedure of mooring.



Any mooring operation requires planning & preparation.



A mooring plan shows the position of the mooring lines to be used.



A minimum of four stations are involved in mooring operations : the bridge,



the engine room,



forward station



and aft station.





On large ships, there can be an additional mooring station amidships.

When the deck parties are ordered “stand-by for mooring”, they prepare mooring lines,





heaving lines,

anchors,



and fenders.





In the engine-room, more generators are put on the board to feed crucial units, like thrusters and winches.

On the bridge, the bridgewing console is prepared.





Effective and constant communication is established between all mooring stations, either using VHF



or a talk-back
system.



Thrusters are operational.

When approaching the berth, the ship's headway is run off.




Officers are posted on special positions to inform the bridge station about the actual distances to the quay,



especially,
when berthing head to or stern to,





when deck cargo
obscures the view
from the bridge



or when other
ships are
berthed close
ahead of the
mooring ship.

The use of CCTV can provide the bridge station with such information.



During dark hours, searchlights are used to obtain a better view.





Fore and aft
stations stand
by for
mooring.

The mooring ropes are coiled



flaked out on deck



and the eyes of the mooring lines are rove through the fairleads.



Here the commanding officer of the forward station has taken position in a special protective cage.





The master and the pilot discuss how to position the ship.

In rare cases, when shore assistance is unavailable, a deckhand jumps ashore.



The ship's head is brought close to the shore, either unassisted



or with tug assistance.

Salvador/Angel L. Godar Moreira
Las Palmas, 12 January 2008






When close enough to the quay, a heaving line is thrown out.

The ship slowly proceeds to her berth,





where a spring or headline can be passed ashore and be put on a specific bollard.

When throwing heaving lines and sending mooring lines ashore, the aft station should prevent fouling the ship's propeller.



Slipknots will make it easier for the linesmen to disconnect the heaving line from the mooring line.



When the distance to the quay is significant, mooring lines are lowered





And passed to a mooring man on board a mooring boat or launch.



The mooring
launch brings
the mooring
lines ashore,




where linesmen
or linehandlers
put the eyes of
the mooring
lines on shore
bollards.

Mooring lines on both ends can be given at once,



if the ship is properly kept in position by tugs.



If there are no linesmen and the distance is small, a mooring line can be thrown over a shore bollard.



When mooring on buoys, a mooring launch assists in bringing the mooring lines to the mooring buoy and making them fast,





When using a slip wire, the eye, that is to be belayed on board, is seized with a rope of a smaller diameter.

Special signs can be made on the quay to indicate the ship's required position.



When the ship is in position,



the mooring teams work their winches.



The commanding officer shows



the winchman to start heaving,



to heave a little bit more,




and to stop heaving when the line comes tight.



Either mooring lines are tended with a mooring winch with storage and tension drums.




or the mooring line is heaved in with the warping drum on a winch,



stoppered,





and belayed to a
bollard

or bitts (two bollards).



A combination of winches and bollards gives the mooring party more possibilities.



Operating mooring winches usually requires a minimum of 2 men.





Here a
capstan is
operated by
remote
control.

As a rule, controls of winches include emergency stop pushbuttons.




Some winches can be operated in automatic (self tension) mode.



Excessive tension on the ropes combined with the poor condition of mooring gear has led to fatal incidents.



Snap-back zones should be avoided.





Once the ship is
moored,
gangways or
accommodation
ladders can be
lowered.

It remains necessary to tend the mooring lines throughout the stay in port.



The departure and actual unmooring starts with the process of singling up :



leaving only a headline, a forward spring, an aft spring and a sternline.



When tugs are in full control, all lines can be let go at once.



When unassisted, a slip rope can be kept in order to assist the manoeuvring and let go when the ship is well clear.

Salvador/Angel L. Godar Moreira
Las Palmas, 23 Januray 2008.



When all ropes are on deck,



the ship can leave the berth.



When the ship is underway, the mooring ropes can be stored



either on deck, like in this cradle,



or below deck in a rope locker.



Here, a Polish apprentice is taking a rest on a coil of mooring ropes



Winches are to be checked and greased.





Thank you
and farewell !