

A Normalisation Example



Based on work by Robert Timmer-Arends

Take the following table.

StudentID is the primary key.

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
					Maths	\$50	A
					Info Tech	\$100	B+

Is it 1NF?

No. There are repeating groups (subject, subjectcost, grade)

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
					Maths	\$50	A
					Info Tech	\$100	B+

How can you make it 1NF?

Create new rows so each cell contains only one value

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
					Maths	\$50	A
					Info Tech	\$100	B+



StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

But now look – is the *studentID* primary key still valid?

No – the studentID no longer uniquely identifies each row

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

You now need to declare *studentID* **and** *subject* **together** to uniquely identify each row.

So the new **key** is StudentID *and* Subject.

So. We now have 1NF.

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

Is it 2NF?

Studentname and **address** are dependent on **studentID** (which is part of the key)

This is good.

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

But they are **not** dependent on *Subject* (the *other* part of the key)

And 2NF requires...

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

All non-key fields are dependent on the ENTIRE key (studentID + subject)

So it's not 2NF

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

How can we fix it?

Make new tables

- Make a new table for each primary key field
- Give each new table its own primary key
- Move columns from the original table to the new table that matches their primary key...

Step 1

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

STUDENT TABLE (key = StudentID)

Step 2

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Step 3

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

RESULTS TABLE (key = StudentID+Subject)

Step 3

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
19594332X	Mary Watson	10 Charles Street	Bob	Red	Maths	\$50	A
19594332X	Mary Watson	10 Charles Street	Bob	Red	Info Tech	\$100	B+

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

RESULTS TABLE (key = StudentID+Subject)

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

Step 4 - relationships

STUDENT TABLE (key = StudentID)


StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



Step 4 - cardinality

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

1

Each student can only appear ONCE in the student table

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)

Step 4 - cardinality

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

Each subject can only appear ONCE in the subjects table

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)

1

1

Step 4 - cardinality

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

A subject can be listed MANY times in the results table (for different students)

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)

1

1

∞

Step 4 - cardinality

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red


SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

A student can be listed MANY times in the results table (for different subjects)

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



A 2NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)

SubjectCost is only dependent on the primary key, *Subject* 😊

A 2NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

Grade is only dependent on the primary key (*studentID + subject*)

RESULTS TABLE (key = StudentID+Subject)



A 2NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

Name, Address are only dependent on the primary key (StudentID)




SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

**So it is
2NF!**

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)

But is it 3NF?



A 3NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red

SUBJECTS TABLE (key = Subject)


Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)

Oh
oh...

What?



A 3NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red


HouseName is dependent on both *StudentID + HouseColour*

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



A 3NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red


Or HouseColour is dependent on both StudentID + HouseName

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



A 3NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red


*But either way,
non-key fields are
dependent on MORE
THAN THE PRIMARY
KEY (studentID)*

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



A 3NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red


*And 3NF says that non-key fields must depend on **nothing** but the key*

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



A 3NF check

STUDENT TABLE (key = StudentID)

StudentID	StudentName	Address	HouseName	HouseColor
19594332X	Mary Watson	10 Charles Street	Bob	Red


WHAT DO WE DO?

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

RESULTS TABLE (key = StudentID+Subject)



Again, carve off the offending fields

StudentTable

StudentID	StudentName	Address	HouseName
19594332X	Mary Watson	10 Charles Street	Bob

Primary key: StudentID

1

∞

∞

1

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

RESULTS TABLE (key = StudentID+Subject)

A 3NF fix

StudentTable

StudentID	StudentName	Address
19594332X	Mary Watson	10 Charles Street

Primary key: StudentID

HouseTable

HouseName	HouseColor
Bob	Red

Primary key: HouseName

1

∞

∞

1

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+

SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100

RESULTS TABLE (key = StudentID+Subject)

A 3NF fix

StudentTable

StudentID	StudentName	Address	HouseName
19594332X	Mary Watson	10 Charles Street	Bob

Primary key: StudentID

HouseTable

HouseName	HouseColor
Bob	Red


Primary key: HouseName

StudentID	Subject	Grade
19594332X	English	B
19594332X	Maths	A
19594332X	Info Tech	B+


SUBJECTS TABLE (key = Subject)

Subject	SubjectCost
English	\$50
Maths	\$50
Info Tech	\$100


RESULTS TABLE (key = StudentID+Subject)



A 3NF win!



Or...




The Reveal

Before...

StudentID	StudentName	Address	HouseName	HouseColor	Subject	SubjectCost	Grade
19594332X	Mary Watson	10 Charles Street	Bob	Red	English	\$50	B
					Maths	\$50	A
					Info Tech	\$100	B+

After...



RESULTS TABLE (key = StudentID+Subject)

SUBJECTS TABLE (key = Subject)

The end

- Thanks to Robert Timmer-Arends for the scenario and staging of the normalisation