# MECHANIC AL WAVE

is a form of disturbance which travels through the medium due to the repeated periodic motion of the particles of the medium about their mean positions, the disturbance being handed over from one particle to the next



A **transverse wave** is a type of wave motion when the particles of the medium vibrate at right angles to the direction of propagation of the wave

A **longitudinal wave** is one in which vibrations occur in the same direction as the direction the wave travels along

#### PROGRESSIVE TRANSVERSE WAVE



Each particle vibrates perpendicular to the direction of propagation with the same amplitude and frequency

Light and all other electromagnetic waves, and water waves are transverse



### PROGRESSIVE LONGITUDINAL WAVE



The displacements of the particles cause regions of high density (compressions) and of low density (rarefactions) to be formed along the wave

Each particle vibrates about its mean position with the same amplitude and frequency

Longitudinal wave is a sound wave. This is propagated by alternate compressions and rarefactions of the air

## **CHARACTERISTICS of MECHANICAL WAVES**



is wave vector directed along the normal to the wave surface. It demonstrates the direction of wave propagation

 $|k| = 2\pi/\lambda$ 

is wave number. It is modulus of wave vector

 $\lambda = vT = \frac{v}{f} = \frac{2\pi v}{\omega}$  is a wavelength



O is point source

### *S*(*A*) is **amplitude** of a wave

The distance travelled by a wave in the time in which the particle of the medium completes one vibration is the **wavelength** 

wave front (there are spherical, plane, cylindrical and other waves depending on the shape of a wavefront)

After time *t* the wave has travelled distance *vt* v is the velocity of the wave The energy of the wave has reached the surface of a sphere of centre O and radius *vt* The surface of the sphere is called the **wavefront** of the wave at this instant. Every point on it is vibrating **in phase** with every other point Source of wave is infinitely long plane

s(x, t)

x

 $\mathbf{x}$ 

1

s(0, t)

x = Vt

0

S

0

WAVE EQUATION

*a*) a plane-progressive wave

$$s(0,t) = s_0 \cos \omega t \quad \tau = x/V$$
  

$$(x,t) = s_0 \cos \omega (t-\tau) = s_0 \cos \omega (t-x/V)$$
  

$$V = \omega/k \quad s(x,t) = s_0 \cos (\omega t - kx)$$

is equation of a *linear-progressive* wave (a *plane-progressive* wave) The negative sign indicates that, since the wave moves from left to right, the vibrations at points such as *P* to the right of *O* will lag that at *O* 

A wave travelling in the *opposite direction*, arrives at *P* before *O*. Thus, the vibration at *P* leads that at *O*.

$$s(x,t) = s_0 \cos(\omega t + kx)$$

General case:

$$s(\overset{\boxtimes}{r},t) = s_0 \cos\left[\omega t - \left(\overset{\boxtimes}{k} \cdot \overset{\boxtimes}{r}\right)\right].$$
$$\begin{pmatrix}\overset{\cong}{k} \cdot \overset{\boxtimes}{r} = k_x x + k_y y + k_z z$$

$$s(\overset{\bowtie}{r},t) = s_0 \cos\left(\omega t - k_x x - k_y y - k_z z\right).$$



λ

### b) a spherical wave



The amplitude of the wave diminishes as distance r from the source O increases. This is caused by the decrease of energy density at larger distances from the source

$$s(\overset{\mathbb{M}}{r},t) = s_0 \cos(\omega t - k_x x - k_y y - k_z z)$$

$$\frac{\partial^2 s}{\partial t^2} = -\omega^2 s_0 \cos(\omega t - k_x x - k_y y - k_z z) = -\omega^2 s_z$$

$$\frac{\partial^2 s}{\partial x^2} = -k_x^2 s_0 \cos(\omega t - k_x x - k_y y - k_z z)$$

$$\frac{\partial^2 s}{\partial y^2} = -k_y^2 s_0 \cos(\omega t - k_x x - k_y y - k_z z)$$

$$\frac{\partial^2 s}{\partial z^2} = -k_z^2 s_0 \cos(\omega t - k_x x - k_y y - k_z z)$$

$$\frac{\partial^2 s}{\partial x^2} + \frac{\partial^2 s}{\partial y^2} + \frac{\partial^2 s}{\partial z^2} = -\left(k_x^2 + k_y^2 + k_z^2\right) s_0 \cos\left(\omega t - k_x x - k_y y - k_z z\right)$$

$$k_x^2 + k_y^2 + k_z^2 = k^2$$

$$s_0 \cos\left(\omega t - k_x x - k_y y - k_z z\right) = s$$

$$\frac{\partial^2 s}{\partial x^2} + \frac{\partial^2 s}{\partial y^2} + \frac{\partial^2 s}{\partial z^2} = -k^2 s$$

$$s = -\frac{1}{\omega^2} \cdot \frac{\partial^2 s}{\partial t^2}$$

$$\frac{\partial^2 s}{\partial x^2} + \frac{\partial^2 s}{\partial y^2} + \frac{\partial^2 s}{\partial z^2} = \frac{k^2}{\omega^2} \cdot \frac{\partial^2 s}{\partial t^2} = \frac{1}{\nu^2} \cdot \frac{\partial^2 s}{\partial t^2}$$

$$\Delta s = \frac{1}{\mathbf{v}^2} \cdot \frac{\partial^2 s}{\partial t^2}$$

is the wave differential equation

### PHASE VELOCITY OF WAVE



If an elastic bar is caused to vibrate by being strucked, an elastic wave begins to propagate along the bar

Phase velocity is  $V = l/\Delta t$  $\Delta t$  is impact duration *l* is displacement of a wave front

Velocity of displacement of bar points after impact is  $u = \Delta l / \Delta t$  $\Delta l$  is displacement of points of a bar end per  $\Delta t$ 

 $\Delta(mu) = mu = F\Delta t. \qquad F\Delta t = mu = \rho lAu = \rho lA\frac{\Delta l}{\Delta t}$   $F = EA\frac{\Delta l}{l} \qquad E \text{ is Young's modulus of elasticity}$   $EA\frac{\Delta l}{l}\Delta t = \rho lA\frac{\Delta l}{\Delta t} = \rho A\Delta l\frac{l}{\Delta t} \qquad \rho \frac{l^2}{\Delta t^2} = \rho v^2 = E.$   $V = \sqrt{E/\rho} \quad \text{is the phase velocity} \quad V = \sqrt{G/\rho} \quad \text{is th} of a$ 

 $V = \sqrt{G/\rho}$  is the phase velocity of a transversal wave *G* is *shear modulus*